

EEVOLUTION

BATTERY SYSTEMS

In Association With



GEN5-2SW

EEvolution Liquid Cooled Battery System



Specification			
Voltage Range:	156V (0%) to 200V (100% SoC)	Capacity:	158.8Ah (27.2kWh)
Max Cont. Discharge Current:	200A Fused	Charge Temperature Range:	- 20°C to 55°C
Max Peak Discharge Current:	600A Fused	Discharge Temperature Range:	- 20°C to 55°C
Mass:	140kg (Estimated)	Storage Temperature Range:	- 30°C to 65°C
Dimensions: 947mm Wide X 664mm Long (Ex Connectors etc.) X 163mm High (Inc Mountings)			

Using Envision AESC GEN5 battery module technology, we have developed liquid cooled battery subsystems that can be connected in series to meet the applications voltage requirements, ranging from 85.1V to 680V (Nominal) at up to 108kWh. If your capacity requirements are higher, then we can use multiple strings in parallel.

Each subsystem contains BMS, Isolation Contactors, Fuse, MSD and HVIL Power Connectors.

Combined with our advanced Battery Management System (BMS), High Voltage Power Distribution Unit (HVPDU) your project to take full advantage of our modular battery solutions and seamless integration with any power system, ensuring maximum safety and performance.

	Document title GEN5-2SW	Issue Date: 2024/03/12	Page 1 of 1
	Document & Revision no. 2.0		